

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number  
**WO 2005/076920 A2**

(51) International Patent Classification: Not classified

(21) International Application Number:  
PCT/US2005/003553

(22) International Filing Date: 4 February 2005 (04.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/541,975 5 February 2004 (05.02.2004) US

(71) Applicant (for all designated States except US):  
**LOMONT MOLDING, INC.** [US/US]; 1516 East  
Mapleleaf Drive, P.O. Box 601, Mt. Pleasant, IA 52641  
(US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WATSON, Virgil,**

A. [US/US]; 1516 East Mapleleaf Drive, P.O. Box 601,  
Mt. Pleasant, IA 52641 (US). **BENDER, Jason** [US/US];  
1516 East Mapleleaf Drive, P.O. Box 601, Mt. Pleasant, IA  
52641 (US).


(74) Agents: **ZARLEY, Timothy, J.** et al.; Capital Square, 400  
Locust Street, Suite 200, Des Moines, IA 50309-2350 (US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: SIGNAGE CONSTRUCTION METHOD AND APPARATUS



(57) Abstract: A sign for viewing by persons in a traffic area accessible by the random passage of persons through the area, the sign including a label formed of a thin layer of plastic material upon which the subject matter of the desired sign is printed. A planar substrate of molded material is fused to the label. The planar substrate includes a mounting feature adapted to secure the sign to a second object. During manufacture, an injection device and ejector system are associated with a first sign mold portion, a label is placed in a second sign mold portion, the first and second sign mold portions are closed together during injection, and the previously formed sign is removed from the first sign mold portion via the ejector system prior to closing the mold portions together.

WO 2005/076920 A2



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *without international search report and to be republished upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*